

The listing of the claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (Currently Amended): A system for transmitting data in a serial bidirectional bus with a control device comprising a send and receiving unit for data fields combined into a data frame, and with bus subscribers which comprise an evaluation circuit for reading in and reading out data fields in data frames, with at least the bus subscriber at the bus end opposite of the control device comprising a send device for a data frame, ~~characterized in that~~ wherein at least the bus subscriber (4) at the end of the bus comprises a control stage (13) which is activated by a received data frame (6) and triggers the send device (12) depending on the receipt of a data frame (6) within the terms of the transmission of a data frame (11) for at least the data fields (14, 15 and 16) of the bus subscribers (2, 3 and 4).

Claim 2 (Currently Amended): A system according to claim 1, ~~characterized in that~~ wherein each of the bus subscribers comprises a control stage (13) for a send device (12) for sending

a data frame (11) for the own data fields and the data fields of the bus subscribers which lie between the control device (1) and the respective bus subscribers.

Claim 3 (Currently Amended): A system according to claim 1 ~~or 2, characterized in that~~ wherein the bus subscribers (2, 3 and 4) comprise a memory (14) for the position of the data fields (7, 8, 9, 14, 15 and 16) within the respective data frame (6, 11), which data fields can be read in and out via the evaluation circuit (10).

Claim 4 (Currently Amended): A system according to claim 3, ~~characterized in that~~ wherein the control device (1) comprises an allocation stage (17) for the position of the data fields (7, 8, 9, 14, 15 and 16) within a data frame (6 or 11) which can be allocated to the individual bus subscribers (2, 3 and 4) and an initialization device (18) for reading out the positional data in data fields of a data frame addressed to the individual bus subscribers, and that the bus subscribers (2, 3 and 4) comprise an initialization circuit (23) for the address-related reading out of the positional data from the addressed data fields of the data frame into the memory (14) for these positional data.

Claim 5 (Currently Amended): A system according to ~~one of~~
~~the claims 1 to 4~~ claim 1, ~~characterized in that~~ wherein each
bus subscriber (2, 3 and 4) comprises a test circuit (24) for
recognizing a bus subscriber (3 and 4) connected to the bus (5)
and connected in outgoing circuit with the same.

Claim 6 (Currently Amended): A system according to ~~one of~~
~~the claims 1 to 5~~ claim 1, ~~characterized in that~~ wherein, as is
known, the control device (1) and the bus subscribers (2, 3 and
4) each comprise an encoding device (25) for producing check data
(16) from the data frame (6 and 11), and that, as is known, the
control device (1) and the bus subscribers (2, 3 and 4) each
comprise a check device (27) for check data received with the
data frames (6 and 11).

Claim 7 (Currently Amended): A system according to ~~one of~~
~~the claims 1 to 6~~ claim 1, ~~characterized in that~~ wherein the
control device (1) comprises an address memory (30) for the
addresses (31) of the bus subscribers and that each bus
subscriber (2, 3 and 4) comprises a recognition circuit (32) for
triggering the evaluation circuit (10) for reading out the data
field (20, 21 or 22) in the data frame (19) addressed to the bus

subscriber (2, 3 or 4) on the one hand and for reading in its data field (28, 29 or 30) into the data frame (27) on the other hand.